Aqueous coating composition, its preparation and utilization.

Patent Number:	EP0436941
Publication date:	1991-07-17
Inventor(s):	SCHWAB MICHAEL DR DIPL-CHEM (DE); KUBILLUS UWE DR DIPL-CHEM (DE)
Applicant(s)::	HOECHST AG (DE)
Requested Patent:	EP0436941, B1
Application Number:	EP19900125657 19901228
Priority Number(s):	DE19904000748 19900112
IPC Classification:	C09D5/02 ; C09D175/04
EC Classification:	C08G18/08B6, C08G18/12, C09D175/04
Equivalents:	BR9100111, CA2033530, CN1053252, DE4000748, ES2052154T, JP7070514, ZA9100222

Abstract

An aqueous coating composition for the manufacture of primers or of filler coatings, which contains at least one water-dispersible binder resin, as well as crosslinking agents and, if appropriate, customary additives, characterised in that the water-dispersible binder resin is at least partly a polyurethane resin which contains components which are derived from (A) polyisocyanates, (B) polyols having an average molecular weight Mn of at least 400, (C) if appropriate low molecular weight polyols, (D) compounds which contain at least two groups which are reactive with isocyanate groups and at least one group capable of anion formation, (E) polyols which carry no further groups reactive with isocyanate groups, where these components (E) are each located on the chain end of the polyurethane resin, if appropriate (F) compounds which are monofunctional or contain active hydrogen of differing reactivity and are different from (E), where these components (F) are also located on the chain end of the polyurethane resin and, if appropriate (G) compounds which are different from (B), (C), (D), (E) and (F) and contain at least two groups reactive with NCO groups. The filler coatings obtainable therefrom are distinguished, inter alia, by improved resistance to flying stones at low temperatures and by good intermediate layer adhesion, while corresponding primers show improved protection against corrosion.